

WIMA QUALITY ASSURANCE

CUSTOMER PCN ACKNOWLEDGEMENT FORM

Part: Metallized Polyester (modified PET) Capacitors

WIMA Type: **WIMA MKS 2-HT/PCM 5mm** 0,01µF through 2,2µF/ 63VDC / 100VDC / 250VDC

Change : to be discontinued due to the termination of production and replaced as of now/as soon as possible (at the end of 2006 latest)on request by

WIMA MKS 2/PCM 5mm

125 °C/0,5UN/2000h distributed on the lifetime of) change of type the capacitor $\ensuremath{$)

or WIMA MKI 2new/PCM 5mm

 $0,01\mu F$ through $1,0\mu F/~63VDC$) change of type /~100VDC) change of type /~250VDC) change of type

There is no impact on electrical and reliability parameters due to these changes!

We confirm that all WIMA PET/PPS capacitors

- are in accordance with data given in the WIMA catalogue 2005/2006
- have been tested and certified according to the IEC generic specification for fixed capacitors for electronic equipment (IEC 60384-1)
- have an encapsulation made of self-extinguishing material according to UL 94V-0
- have been tested 100% for all electrical parameters inclusive dielectric strength

Signature: Roland Wilhelm

Function: Technical Support

Date: September, 2006

i.f. Gulle