

WIMA QUALITY ASSURANCE

CUSTOMER PCN ACKNOWLEDGEMENT FORM

Part: Metallized Polypropylene (PP) Capacitors

WIMA Type: WIMA MKP 2/PCM 5mm

1000pF through 6800pF/ 63VDC

/ 100VDC / 250VDC

and

1000pF and 1500pF / 1000VDC 2,5x6,5x7,2/PCM 5

1000pF through 3300pF/ 400VDC 2,5x6,5x7,2/PCM 5

/ 630VDC 2,5x6,5x7,2/PCM 5

 $0.01\mu F$ and $0.015\mu F$ / 63VDC 2.5x6.5x7.2/PCM 5

/ 100VDC 2,5x6,5x7,2/PCM 5

 $0.01\mu F$ / 250VDC 2,5x6,5x7,2/PCM 5

Change: to be discontinued or modified respectively due to the change

of equipment and replaced as of now/as soon as possible

(at the end of 2006 latest) by

WIMA MKP 2/PCM 5mm \rightarrow U_R)change of U_R

and

1000pF and 1500pF / 1000VDC 3x7,5x7,2/PCM 5)change of dimensions

1000pF through 3300pF/ 400VDC 3x7,5x7,2/PCM 5)change of dimensions

/ 630VDC 3x7,5x7,2/PCM 5)change of dimensions

 $0.01\mu\text{F}$ and $0.015\mu\text{F}$ / 63VDC 3x7.5x7.2/PCM 5)change of dimensions

/ 100VDC 3x7,5x7,2/PCM 5)change of dimensions

 $0.01\mu F$ / 250VDC 3x7,5x7,2/PCM 5)change of dimensions

There is no impact on electrical and reliability parameters due to these changes!

We confirm that all WIMA PP capacitors

- are in accordance with data given in the WIMA catalogue 2005/2006

i.f. Glille

- have been tested and certified according to the IEC generic specification for fixed capacitors for electronic equipment (IEC 60384-1)
- have an encapsulation made of self-extinguishing material according to UL 94V-0
- have been tested 100% for all electrical parameters inclusive dielectric strength

Signature: Roland Wilhelm Function: Technical Support

Date: September, 2006