



W I M A QUALITY ASSURANCE

CUSTOMER PCN ACKNOWLEDGEMENT FORM

Part: Metallized Polypropylene (PP) Capacitors

WIMA Type: **WIMA MKP 4/PCM 7.5mm through 37.5mm**

1000pF through 6800pF / 100VDC
/ 250VDC
/ 400VDC
/ 630VDC
/ 1000VDC

and

0,01µF through 0,022µF / 100VDC 2,5x7x10/PCM 7,5
/ 250VDC 2,5x7x10/PCM 7,5
0,01µF / 400VDC 2,5x7x10/PCM 7,5

as well as

lead diameter PCM 7,5mm B ≥ 4mm Ø 0,7mm
lead diameter PCM 10mm B ≥ 4mm Ø 0,7mm
lead diameter PCM 27,5mm B > 15mm Ø 1,0mm

Change : to be discontinued or modified respectively due to the change of equipment and replaced as of now/as soon as possible (at the end of 2006 latest) by

WIMA FKP 3/PCM 7.5mm through 15mm)change of type
or **WIMA MKP 10/PCM 7.5mm through 37.5mm**)change of type

and

0,01µF through 0,022µF/100VDC 3x8,5x10/PCM 7,5)change of dimensions
/250VDC 3x8,5x10/PCM 7,5)change of dimensions
0,01µF /400VDC 3x8,5x10/PCM 7,5)change of dimensions

as well as

lead diameter PCM 7,5mm B ≥ 4mm Ø 0,6mm)change of lead diameter
lead diameter PCM 10mm B ≥ 4mm Ø 0,6mm)change of lead diameter
lead diameter PCM 27,5mm B > 15mm Ø 0,8mm)change of lead diameter

There is no impact on electrical and reliability parameters due to these changes!

We confirm that all WIMA PP capacitors

- are in accordance with data given in the WIMA catalogue 2005/2006
- have been tested and certified according to the IEC generic specification for fixed capacitors for electronic equipment (IEC 60384-1)
- have an encapsulation made of self-extinguishing material according to UL 94V-0
- have been tested 100% for all electrical parameters inclusive dielectric strength

Signature: Roland Wilhelm

Function: Technical Support

Date: September, 2006