

Metallized Polypropylene (PP) - Capacitors in Cylindrical Case.
MKP 6 with High Volume/Capacitance Ratio, MKP 6 HP with Higher Current Carrying Capability. Capacitances from 75 µF to 4920 µF. Rated Voltages from 600 VDC to 1500 VDC.

Special Features

- Very high volume/capacitance ratio
- Self-healing properties
- With cylindrical aluminium case for bus bar mounting
- Dry construction without electrolyte or oil
- No internal fuse required
- Negative capacitance change versus temperature
- Very low dielectric absorption
- According to RoHS 2011/65/EU
- Customer-specific capacitances or voltages on request

Typical Applications

DC capacitors with high capacitances for applications in power electronics also at non-sinusoidal voltages and currents e.g. in

- Wind power systems
- Inverters

Construction


Dielectric:

Polypropylene (PP) film

Capacitor electrodes:

Vacuum-deposited

Internal construction:



Encapsulation:

Aluminium case with PU-sealing, UL 94 V-0

Terminations:

Screw connection (male or female), screw bolt M12 x 16.

Marking:

Colour: Metallic. Marking: Black on silver label.

Electrical Data

Capacitance range: 75 µF to 4920 µF
Rated voltages: 600 VDC, 700 VDC, 900 VDC, 1100 VDC, 1300 VDC, 1500 VDC
Capacitance tolerances: ±20%, ±10% (±5% available subject to special enquiry)
Operating temperature range: -40° C to +85° C
Insulation resistance at +20° C:
 ≥ 5000 sec (MΩ x µF)
 Measuring voltage: 100 V/1 min.

Dielectric loss factor $\tan \delta_0$: 2×10^{-4}

Test voltage between terminals

at +25° C: $1.5 U_{rDC}$, 10sec

Test voltage between terminals and case

at +25° C and 50 Hz: $3 kV_{AC}$, 1 min.

Dielectric absorption:

0.05 %

Reliability:

Operational life > 100 000 hours

Failure rate < 50 fit (hot spot ≤ 70° C)


Mounting Recommendation

Excessive mechanical strain, e.g. pressure or shock onto the capacitor body, is to be avoided during mounting and usage of the capacitors.

Packing

Transportation-safe packing in cardboard boxes.

For further details and graphs please refer to Technical Information.



The capacitors are non-polarized and are optionally available with „male“ and „female“ terminations. The earth bolt is electrically inactive and serves for fixing and/or earthing of the metal case.

Continuation

General Data

U_R		C_N	D x L mm	I_{rms} (max.)* at 70°C A	ESR (1 kHz)* mΩ	L_e nH	Approx. weight g	Part number
70° C	85° C							
600 VDC	450 VDC	320 μF	85 x 60	25	2.1	< 40	380	DCP6I06320EB00_
		460 "	85 x 76	25	2.1	< 40	480	DCP6I06460EC00_
		520 "	85 x 85	30	2.0	< 40	540	DCP6I06520ED00_
		620 "	85 x 95	30	1.9	< 40	600	DCP6I06620EE00_
		760 "	85 x 110	30	1.7	< 40	690	DCP6I06760EF00_
		780 "	85 x 120	30	1.7	< 40	700	DCP6I06780E000_
		950 "	85 x 132	35	1.8	< 40	850	DCP6I06950E100_
		1030 "	85 x 140	35	1.8	< 40	880	DCP6I07103EG00_
		1220 "	116 x 95	40	1.7	< 40	1200	DCP6I07122EN00_
		1500 "	116 x 110	40	1.7	< 40	1390	DCP6I07150EO00_
		1640 "	116 x 120	40	1.6	< 40	1510	DCP6I07164EP00_
		1890 "	116 x 132	40	1.6	< 40	1660	DCP6I07189EQ00_
		2030 "	116 x 140	40	1.6	< 40	1760	DCP6I07203ER00_
700 VDC	600 VDC	230 μF	85 x 60	25	1.9	< 40	380	DCP6K06230EB00_
		330 "	85 x 76	25	1.9	< 40	480	DCP6K06330EC00_
		380 "	85 x 85	30	1.7	< 40	540	DCP6K06380ED00_
		450 "	85 x 95	30	1.7	< 40	600	DCP6K06450EE00_
		550 "	85 x 110	30	1.8	< 40	690	DCP6K06550EF00_
		585 "	85 x 120	30	1.8	< 40	700	DCP6K06585E000_
		690 "	85 x 132	35	1.8	< 40	850	DCP6K06690E100_
		740 "	85 x 140	35	1.8	< 40	880	DCP6K06740EG00_
		890 "	116 x 95	40	1.7	< 40	1200	DCP6K06890EN00_
		1090 "	116 x 110	40	1.7	< 40	1390	DCP6K07109EO00_
		1190 "	116 x 120	40	1.8	< 40	1510	DCP6K07119EP00_
		1370 "	116 x 132	40	1.8	< 40	1660	DCP6K07137EQ00_
		1470 "	116 x 140	40	1.8	< 40	1760	DCP6K07147ER00_
900 VDC	760 VDC	190 μF	85 x 60	30	1.9	< 40	380	DCP6N06190EB00_
		270 "	85 x 76	30	1.9	< 40	480	DCP6N06270EC00_
		315 "	85 x 85	30	1.8	< 40	540	DCP6N06315ED00_
		360 "	85 x 95	30	1.7	< 40	600	DCP6N06360EE00_
		450 "	85 x 110	30	1.7	< 40	690	DCP6N06450EF00_
		480 "	85 x 120	35	1.8	< 40	700	DCP6N06480E000_
		550 "	85 x 132	35	1.8	< 40	850	DCP6N06550E100_
		620 "	85 x 140	35	1.8	< 40	880	DCP6N06620EG00_
		730 "	116 x 95	40	1.7	< 40	1200	DCP6N06730EN00_
		900 "	116 x 110	40	1.7	< 40	1390	DCP6N06900EO00_
		980 "	116 x 120	40	1.8	< 40	1510	DCP6N06980EP00_
		1130 "	116 x 132	40	1.8	< 40	1660	DCP6N07113EQ00_
		1200 "	116 x 140	40	1.8	< 40	1760	DCP6N07120ER00_
1100 VDC	920 VDC	120 μF	85 x 60	30	2.0	< 40	380	DCP6P06120EB00_
		170 "	85 x 76	30	2.0	< 40	480	DCP6P06170EC00_
		200 "	85 x 85	30	1.9	< 40	540	DCP6P06200ED00_
		230 "	85 x 95	30	1.9	< 40	600	DCP6P06230EE00_
		290 "	85 x 110	30	1.8	< 40	690	DCP6P06290EF00_
		325 "	85 x 120	40	1.8	< 40	700	DCP6P06325E000_
		360 "	85 x 132	40	1.8	< 40	850	DCP6P06360E100_
		390 "	85 x 140	40	2.0	< 40	880	DCP6P06390EG00_
		470 "	116 x 95	40	1.8	< 40	1200	DCP6P06470EN00_
		580 "	116 x 110	40	1.8	< 40	1390	DCP6P06580EO00_
		630 "	116 x 120	40	1.7	< 40	1510	DCP6P06630EP00_
		720 "	116 x 132	40	1.7	< 40	1660	DCP6P06720EQ00_
		780 "	116 x 140	40	1.6	< 40	1760	DCP6P06780ER00_

Contacts can handle: peak currents \hat{I} up to 5 kA
surge currents I_S up to 20 kA

Customer-specific capacitances or voltages on request

* General guide

Part number completion:	
Tolerance:	20 % = M 10 % = K 5 % = J
Packing:	bulk = S
Connection:	male = OM female = OF

Rights reserved to amend design data without prior notification.

Continuation

General Data


U_R		C_N	D x L mm	I_{rms} (max.)* at 70°C A	ESR (1 kHz)* mΩ	L_e nH	Approx. weight g	Part number
70° C	85° C							
1300 VDC	1100 VDC	85 μF	85 x 60	30	2.1	< 40	380	DCP6R25850EB00_
		120 "	85 x 76	30	2.1	< 40	480	DCP6R26120EC00_
		135 "	85 x 85	30	1.9	< 40	540	DCP6R26135ED00_
		160 "	85 x 95	30	1.9	< 40	600	DCP6R26160EE00_
		200 "	85 x 110	30	1.8	< 40	690	DCP6R26200EF00_
		215 "	85 x 120	30	1.8	< 40	700	DCP6R26215EO00_
		250 "	85 x 132	40	2.2	< 40	850	DCP6R26250E100_
		270 "	85 x 140	40	2.2	< 40	880	DCP6R26270EG00_
		320 "	116 x 95	40	1.8	< 40	1200	DCP6R26320EN00_
		390 "	116 x 110	40	1.8	< 40	1390	DCP6R26390EO00_
		430 "	116 x 120	40	1.7	< 40	1510	DCP6R26430EP00_
		490 "	116 x 132	40	1.7	< 40	1660	DCP6R26490EQ00_
		530 "	116 x 140	40	1.6	< 40	1760	DCP6R26530ER00_
		1500 VDC	1250 VDC	75 μF	85 x 60	25	2.5	< 40
110 "	85 x 76			25	2.5	< 40	480	DCP6S06110EC00_
120 "	85 x 85			25	2.3	< 40	540	DCP6S06120ED00_
145 "	85 x 95			30	2.3	< 40	600	DCP6S06145EE00_
180 "	85 x 110			30	2.3	< 40	690	DCP6S06180EF00_
195 "	85 x 120			40	2.4	< 40	700	DCP6S06195EO00_
225 "	85 x 132			40	2.4	< 40	850	DCP6S06225E100_
240 "	85 x 140			40	2.5	< 40	880	DCP6S06240EG00_
290 "	116 x 95			40	1.8	< 40	1200	DCP6S06290EN00_
355 "	116 x 110			40	1.8	< 40	1390	DCP6S06355EO00_
390 "	116 x 120			40	1.7	< 40	1510	DCP6S06390EP00_
445 "	116 x 132			40	1.7	< 40	1660	DCP6S06445EQ00_
480 "	116 x 140			40	1.7	< 40	1760	DCP6S06480ER00_

Contacts can handle: peak currents \hat{I} up to 5 kA
surge currents I_S up to 20 kA


Customer-specific capacitances or voltages on request

* General guide

female



male



Part number completion:	
Tolerance:	20 % = M
	10 % = K
	5 % = J
Packing:	bulk = S
Connection:	male = 0M
	female = 0F

D	L	a	b	c
85	60	32	12	6
85	76	32	12	6
85	85	32	12	6
85	95	32	12	6
85	110	32	12	6
85	120	32	12	6
85	132	32	12	6
85	140	32	12	6
116	95	50	14	5
116	110	50	14	5
116	120	50	14	5
116	132	50	14	5
116	140	50	14	5

Dims. in mm.

Rights reserved to amend design data without prior notification.

Continuation: Versions with increased dimensioning for higher current carrying capability

General Data

U_R		C_N	D x L mm	I_{rms} (max.)* at 70°C A	ESR (1 kHz)* mΩ	L_e nH	Approx. weight g	Part number
70°C	85°C							
600 VDC	450 VDC	640 μF	85 x 110	50	1.3	< 40	690	DCHPI06640EF00_
		920 "	85 x 140	50	1.3	< 40	880	DCHPI06920EG00_
		1040 "	85 x 155	60	1.3	< 40	980	DCHPI07104EH00_
		1240 "	85 x 185	60	1.3	< 60	1165	DCHPI07124EI00_
		1520 "	85 x 210	60	1.2	< 60	1400	DCHPI07152E200_
		1660 "	85 x 235	60	1.2	< 60	1480	DCHPI07166EJ00_
		1900 "	85 x 252	60	1.2	< 60	1590	DCHPI07190EK00_
		2060 "	85 x 260	60	1.2	< 60	1640	DCHPI07206EL00_
		2490 "	85 x 345	70	1.0	< 70	2190	DCHPI07249EM00_
		1260 "	116 x 110	80	1.2	< 40	1385	DCHPI07126EO00_
		1820 "	116 x 140	80	1.2	< 40	1765	DCHPI07182ER00_
		2060 "	116 x 158	80	1.1	< 40	1990	DCHPI07206ES00_
		2440 "	116 x 185	80	1.1	< 60	2330	DCHPI07244ET00_
		3000 "	116 x 215	80	1.0	< 60	2710	DCHPI07300EU00_
		3280 "	116 x 230	90	1.0	< 60	2900	DCHPI07328E700_
		3780 "	116 x 255	90	1.0	< 60	3210	DCHPI07378EV00_
		4060 "	116 x 295	90	1.0	< 70	3720	DCHPI07406EW00_
		4920 "	116 x 342	100	0.7	< 70	4350	DCHPI07492EX00_
700 VDC	600 VDC	460 μF	85 x 110	50	1.3	< 40	690	DCHPK06460EF00_
		660 "	85 x 140	50	1.3	< 40	880	DCHPK06660EG00_
		760 "	85 x 155	60	1.2	< 40	980	DCHPK06760EH00_
		900 "	85 x 185	60	1.2	< 60	1165	DCHPK06900EI00_
		1100 "	85 x 210	60	1.2	< 60	1400	DCHPK07110E200_
		1200 "	85 x 235	60	1.2	< 60	1480	DCHPK07120EJ00_
		1380 "	85 x 252	70	1.1	< 60	1590	DCHPK07138EK00_
		1480 "	85 x 260	70	1.1	< 60	1640	DCHPK07148EL00_
		1800 "	85 x 345	80	1.0	< 70	2190	DCHPK07180EM00_
		920 "	116 x 110	80	1.3	< 40	1385	DCHPK06920EO00_
		1320 "	116 x 140	80	1.3	< 40	1765	DCHPK07132ER00_
		1500 "	116 x 158	80	1.3	< 40	1990	DCHPK07150ES00_
		1780 "	116 x 185	80	1.2	< 60	2330	DCHPK07178ET00_
		2180 "	116 x 215	90	1.2	< 60	2710	DCHPK07218EU00_
		2380 "	116 x 230	90	1.0	< 60	2900	DCHPK07238E700_
		2740 "	116 x 255	90	1.0	< 60	3210	DCHPK07274EV00_
		2940 "	116 x 295	90	1.0	< 70	3720	DCHPK07294EW00_
		3570 "	116 x 342	110	0.7	< 70	4350	DCHPK07357EX00_
900 VDC	760 VDC	380 μF	85 x 110	50	1.4	< 40	690	DCHPN06380EF00_
		540 "	85 x 140	50	1.4	< 40	880	DCHPN06540EG00_
		630 "	85 x 155	60	1.3	< 40	980	DCHPN06630EH00_
		720 "	85 x 185	60	1.3	< 60	1165	DCHPN06720EI00_
		900 "	85 x 210	60	1.1	< 60	1400	DCHPN06900E200_
		1000 "	85 x 235	70	1.0	< 60	1480	DCHPN07100EJ00_
		1140 "	85 x 252	70	0.9	< 60	1590	DCHPN07114EK00_
		1240 "	85 x 260	70	0.9	< 60	1640	DCHPN07124EL00_
		1500 "	85 x 345	80	0.7	< 70	2190	DCHPN07150EM00_

Contacts can handle: peak currents \hat{I} up to 10 kA
surge currents I_S up to 40 kA

Customer-specific capacitances or voltages on request

* General guide

Part number completion:

Tolerance: 20 % = M
10 % = K
5 % = J
Packing: bulk = S
Connection: male = OM
female = OF

Rights reserved to amend design data without prior notification.

Continuation page 138

Continuation

General Data

U_R		C_N	D x L mm	I_{rms} (max.)* at 70°C A	ESR (1 kHz)* mΩ	L_e nH	Approx. weight g	Part number
70° C	85° C							
900 VDC	760 VDC	760 μF	116 x 110	80	1.3	< 40	1385	DCHPN06760EO00
		1100 "	116 x 140	80	1.3	< 40	1765	DCHPN07110ER00
		1240 "	116 x 158	80	1.3	< 40	1990	DCHPN07124ES00
		1460 "	116 x 185	80	1.2	< 60	2330	DCHPN07146ET00
		1800 "	116 x 215	90	1.2	< 60	2710	DCHPN07180EU00
		1960 "	116 x 230	90	1.0	< 60	2900	DCHPN07196E700
		2260 "	116 x 255	90	1.0	< 60	3210	DCHPN07226EV00
		2400 "	116 x 295	90	1.0	< 70	3720	DCHPN07240EW00
		2940 "	116 x 342	110	0.7	< 70	4350	DCHPN07294EX00
		1100 VDC	920 VDC	240 μF	85 x 110	50	1.3	< 40
340 "	85 x 140			50	1.2	< 40	880	DCHPP06340EG00
400 "	85 x 155			50	1.2	< 40	980	DCHPP06400EH00
460 "	85 x 185			50	1.2	< 60	1165	DCHPP06460EI00
580 "	85 x 210			60	1.2	< 60	1400	DCHPP06580E200
640 "	85 x 235			60	1.1	< 60	1480	DCHPP06640EJ00
720 "	85 x 252			60	1.1	< 60	1590	DCHPP06720EK00
780 "	85 x 260			60	1.2	< 60	1640	DCHPP06780EL00
960 "	85 x 345			80	1.0	< 70	2190	DCHPP06960EM00
480 "	116 x 110			80	1.4	< 40	1385	DCHPP06480EO00
700 "	116 x 140			80	1.3	< 40	1765	DCHPP06700ER00
780 "	116 x 158			80	1.3	< 40	1990	DCHPP06780ES00
940 "	116 x 185			80	1.3	< 60	2330	DCHPP06940ET00
1160 "	116 x 215			90	1.2	< 60	2710	DCHPP07116EU00
1260 "	116 x 230			90	1.2	< 60	2900	DCHPP07126E700
1440 "	116 x 255			90	1.1	< 60	3210	DCHPP07144EV00
1560 "	116 x 295			90	1.0	< 70	3720	DCHPP07156EW00
1890 "	116 x 342			110	0.8	< 70	4350	DCHPP07189EX00
1300 VDC	1100 VDC	170 μF	85 x 110	50	1.3	< 40	690	DCHPR26170EF00
		240 "	85 x 140	50	1.3	< 40	880	DCHPR26240EG00
		270 "	85 x 155	50	1.2	< 40	980	DCHPR26270EH00
		320 "	85 x 185	60	1.2	< 60	1165	DCHPR26320EI00
		400 "	85 x 210	60	1.2	< 60	1400	DCHPR26400E200
		440 "	85 x 235	60	1.1	< 60	1480	DCHPR26440EJ00
		500 "	85 x 252	60	1.1	< 60	1590	DCHPR26500EK00
		540 "	85 x 260	60	1.2	< 60	1640	DCHPR26540EL00
		660 "	85 x 345	80	1.0	< 70	2190	DCHPR26660EM00
		330 "	116 x 110	80	1.4	< 40	1385	DCHPR26330EO00
		480 "	116 x 140	80	1.4	< 40	1765	DCHPR26480ER00
		540 "	116 x 158	80	1.3	< 40	1990	DCHPR26540ES00
		640 "	116 x 185	80	1.3	< 60	2330	DCHPR26640ET00
		780 "	116 x 215	90	1.2	< 60	2710	DCHPR26780EU00
		860 "	116 x 230	90	1.2	< 60	2900	DCHPR26860E700
		980 "	116 x 255	90	1.1	< 60	3210	DCHPR26980EV00
		1060 "	116 x 295	90	1.1	< 70	3720	DCHPR27106EV00
		1290 "	116 x 342	110	0.8	< 70	4350	DCHPR27129EX00

Contacts can handle: peak currents \hat{I} up to 10 kA
surge currents I_s up to 40 kA

Customer-specific capacitances or voltages on request

* General guide

Part number completion:

Tolerance: 20 % = M

10 % = K

5 % = J

Packing: bulk = S

Connection: male = OM

female = OF

Rights reserved to amend design data without prior notification.

Continuation page 139

Continuation


General Data

U_R		C_N	D x L mm	I_{rms} (max.)* at 70°C A	ESR (1 kHz)* mΩ	L_e nH	Approx. weight g	Part number
70° C	85° C							
1500 VDC	1250 VDC	150 μF	85 x 110	50	1.3	< 40	690	DCHPS06150EF00_
		220 "	85 x 140	50	1.3	< 40	880	DCHPS06220EG00_
		240 "	85 x 155	50	1.2	< 40	980	DCHPS06240EH00_
		290 "	85 x 185	60	1.2	< 60	1165	DCHPS06290EI00_
		360 "	85 x 210	60	1.2	< 60	1400	DCHPS06360E200_
		390 "	85 x 235	60	1.1	< 60	1480	DCHPS06390EJ00_
		450 "	85 x 252	60	1.1	< 60	1590	DCHPS06450EK00_
		480 "	85 x 260	60	1.1	< 60	1640	DCHPS06480EL00_
		585 "	85 x 345	80	1.0	< 70	2190	DCHPS06585EM00_
		300 "	116 x 110	80	1.5	< 40	1385	DCHPS06300EO00_
		430 "	116 x 140	80	1.4	< 40	1765	DCHPS06430ER00_
		490 "	116 x 158	80	1.4	< 40	1990	DCHPS06490ES00_
		580 "	116 x 185	80	1.4	< 60	2330	DCHPS06580ET00_
		710 "	116 x 215	90	1.3	< 60	2710	DCHPS06710EU00_
		780 "	116 x 230	90	1.2	< 60	2900	DCHPS06780E700_
		890 "	116 x 255	90	1.2	< 60	3210	DCHPS06890EV00_
		960 "	116 x 295	90	1.1	< 70	3720	DCHPS06960EW00_
		1170 "	116 x 342	110	0.8	< 70	4350	DCHPS07117EX00_

Contacts can handle: peak currents \hat{I} up to 10 kA
surge currents I_S up to 40 kA

Customer-specific capacitances or voltages on request

* General guide



Part number completion:

Tolerance: 20 % = M
10 % = K
5 % = J
Packing: bulk = S
Connection: male = OM
female = OF

D	L	a	b	c
85	110	32	12	6
85	140	32	12	6
85	155	32	12	6
85	185	32	12	6
85	210	32	12	6
85	235	32	12	6
85	252	32	12	6
85	260	32	12	6
85	345	32	12	6
116	110	50	14	5
116	140	50	14	5
116	158	50	14	5
116	185	50	14	5
116	215	50	14	5
116	230	50	14	5
116	255	50	14	5
116	295	50	14	5
116	342	50	14	5

Dims. in mm.

Rights reserved to amend design data without prior notification.



WIMA Part Number System

A WIMA part number consists of 18 digits and is composed as follows:

- Field 1 - 4: Type description
- Field 5 - 6: Rated voltage
- Field 7 - 10: Capacitance
- Field 11 - 12: Size and PCM
- Field 13 - 14: Version code (e.g. Snubber versions)
- Field 15: Capacitance tolerance
- Field 16: Packing
- Field 17 - 18: Pin length (untaped)

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
M	K	S	2	C	0	2	1	0	0	1	A	0	0	M	S	S	D
MKS 2				63 VDC		0.01 µF			2.5x6.5x7.2		-		20%	bulk	6-2		
Type description:				Rated voltage:		Capacitance:			Size:		Tolerance:			Packing:			
SMD-PET = SMDT				50 VDC = B0		22 pF = 0022			4.8x3.3x3 Size 1812 = KA		±20% = M			AMMO H16.5 340x340 = A			
SMD-PEN = SMDN				63 VDC = C0		47 pF = 0047			4.8x3.3x4 Size 1812 = KB		±10% = K			AMMO H16.5 490x370 = B			
SMD-PPS = SMDI				100 VDC = D0		100 pF = 0100			5.7x5.1x3.5 Size 2220 = QA		±5% = J			AMMO H18.5 340x340 = C			
FKP 02 = FKPO				250 VDC = F0		150 pF = 0150			5.7x5.1x4.5 Size 2220 = QB		±2.5% = H			AMMO H18.5 490x370 = D			
MKS 02 = MKS0				400 VDC = G0		220 pF = 0220			7.2x6.1x3 Size 2824 = TA		±1% = E			REEL H16.5 360 = F			
FKS 2 = FKS2				450 VDC = H0		330 pF = 0330			7.2x6.1x5 Size 2824 = TB		...			REEL H16.5 500 = H			
FKP 2 = FKP2				520 VDC = H2		470 pF = 0470			10.2x7.6x5 Size 4030 = VA					REEL H18.5 360 = I			
FKS 3 = FKS3				600 VDC = I0		680 pF = 0680			12.7x10.2x6 Size 5040 = XA					REEL H18.5 500 = J			
FKP 3 = FKP 3				630 VDC = J0		1000 pF = 1100			15.3x13.7x7 Size 6054 = YA					ROLL H16.5 = N			
MKS 2 = MKS2				700 VDC = K0		1500 pF = 1150			2.5x7x4.6 PCM 2.5 = 0B					ROLL H18.5 = O			
MKP 2 = MKP2				800 VDC = L0		2200 pF = 1220			3x7.5x4.6 PCM 2.5 = 0C					BLISTER W12 180 = P			
MKS 4 = MKS4				850 VDC = M0		3300 pF = 1330			2.5x6.5x7.2 PCM 5 = 1A					BLISTER W12 330 = Q			
MKP 4C = MKPC				900 VDC = N0		4700 pF = 1470			3x7.5x7.2 PCM 5 = 1B					BLISTER W16 330 = R			
MKP 4 = MKP4				1000 VDC = O1		6800 pF = 1680			2.5x7x10 PCM 7.5 = 2A					BLISTER W24 330 = T			
MKP 10 = MKP1				1100 VDC = P0		0.01 µF = 2100			3x8.5x10 PCM 7.5 = 2B					Bulk/TPS Standard = S			
FKP 1 = FKP1				1200 VDC = Q0		0.022 µF = 2220			3x9x13 PCM 10 = 3A					...			
MKP-X2 = MKX2				1250 VDC = R0		0.047 µF = 2470			4x9x13 PCM 10 = 3C								
MKP-X1 R = MKX1				1500 VDC = S0		0.1 µF = 3100			5x11x18 PCM 15 = 4B								
MKP-Y2 = MKY2				1600 VDC = T0		0.22 µF = 3220			6x12.5x18 PCM 15 = 4C								
MP 3-X2 = MPX2				2000 VDC = U0		0.47 µF = 3470			5x14x26.5 PCM 22.5 = 5A								
MP 3-X1 = MPX1				2500 VDC = V0		1 µF = 4100			6x15x26.5 PCM 22.5 = 5B								
MP 3-Y2 = MPY2				3000 VDC = W0		2.2 µF = 4220			9x19x31.5 PCM 27.5 = 6A								
MP 3R-Y2 = MPRY				4000 VDC = X0		4.7 µF = 4470			11x21x31.5 PCM 27.5 = 6B								
MKP 4F = MKPF				6000 VDC = Y0		10 µF = 5100			9x19x41.5 PCM 37.5 = 7A								
Snubber MKP = SNMP				250 VAC = 0W		22 µF = 5220			11x22x41.5 PCM 37.5 = 7B								
Snubber FKP = SNFF				275 VAC = 1W		47 µF = 5470			19x31x56 PCM 48.5 = 8D								
GTO MKP = GTOM				300 VAC = 2W		100 µF = 6100			25x45x57 PCM 52.5 = 9D								
DC-LINK MKP 3 = DCP3				305 VAC = AW		220 µF = 6220			...								
DC-LINK MKP 4 = DCP4				350 VAC = BW		1000 µF = 7100											
DC-LINK MKP 4S = DCP4S				440 VAC = 4W		1500 µF = 7150											
DC-LINK MKP 5 = DCP5				500 VAC = 5W		...											
DC-LINK MKP 6 = DCP6				...													
DC-LINK HC = DCHC																	
DC-LINK HY = DCHY																	
									Version code:					Pin length (untaped)			
									Standard = 00					3.5 ±0.5 = C9			
									Version A1 = 1A					6-2 = SD			
									Version A1.1.1 = 1B					16 ±1 = P1			
									Version A2 = 2A					...			
									...					Pin length (taped)			
														none = 00			

The data on this page is not complete and serves only to explain the part number system. Part number information is listed on the pages of the respective WIMA range.